

# SAFETY DATA SHEET

## AUTOTEK VHT ENAMEL MATT BLACK 250ML

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name AUTOTEK VHT ENAMEL MATT BLACK 250ML  
Product No. ATOOVHTBK250

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

#### 1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited  
4 Howarth Court,  
Gateway Crescent, Chadderton,  
Oldham, Lancashire  
OL9 9XB  
England  
0161 627 0101  
sds@jamesbriggs.co.uk

#### 1.4. Emergency telephone number

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Skin Irrit. 2 - H315
Environment	Not classified.

Classification (1999/45/EEC)

Xi;R38. R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Contains XYLENE

Label In Accordance With (EC) No. 1272/2008



Signal Word Warning

Hazard Statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280	Wear protective gloves.
P271	Use only outdoors or in a well-ventilated area.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P501	Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P403+235	Store in a well-ventilated place. Keep cool.
----------	--

#### 2.3. Other hazards

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# AUTOTEK VHT ENAMEL MATT BLACK 250ML

## 3.2. Mixtures

XYLENE		60-100%
CAS-No.: 1330-20-7	EC No.: 215-535-7	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Flam. Liq. 3 - H226	R10	
Acute Tox. 4 - H312	Xn;R20/21	
Acute Tox. 4 - H332	Xi;R38	
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
STOT SE 3 - H335		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		
Aquatic Chronic 3 - H412		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

General information

NOTE! Effects may be delayed. Keep affected person under observation. NOTE! Keep affected person away from heat, sparks and flames!

Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Ingestion

Remove victim immediately from source of exposure. Rinse mouth thoroughly. NOTE! Keep affected person away from heat, sparks and flames! DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media

Use: Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist. Carbon dioxide (CO2).

### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Vapours are heavier than air and may spread near ground to sources of ignition.

### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Ventilate closed spaces before entering them. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Be aware of danger for fire to re-start. Keep run-off water out of sewers and water sources. Dike for water control.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

# AUTOTEK VHT ENAMEL MATT BLACK 250ML

## 6.2. Environmental precautions

## 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Small quantities may be flushed to drains with plenty of water.

## 6.4. Reference to other sections

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

#### 7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Keep containers tightly closed.

Storage Class

Flammable liquid storage.

#### 7.3. Specific end use(s)

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

#### 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated.

Promptly remove any clothing that becomes wet or contaminated. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# AUTOTEK VHT ENAMEL MATT BLACK 250ML

## **9.1. Information on basic physical and chemical properties**

Appearance	Liquid
Colour	Typical
Odour	Characteristic.

## **9.2. Other information**

### **SECTION 10: STABILITY AND REACTIVITY**

#### **10.1. Reactivity**

#### **10.2. Chemical stability**

Stable under normal temperature conditions.

#### **10.3. Possibility of hazardous reactions**

#### **10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

#### **10.5. Incompatible materials**

#### **10.6. Hazardous decomposition products**

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **11.1. Information on toxicological effects**

##### Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

##### Ingestion

May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

##### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. May cause allergic contact eczema.

##### Eye contact

Irritating to eyes. Irritation, burning, lachrymation, blurred vision after liquid splash.

##### Health Warnings

Repeated exposure may cause chronic eye irritation. Swallowing concentrated chemical may cause severe internal injury.

##### Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

##### Medical Symptoms

Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of the nasal mucous membranes).

### **SECTION 12: ECOLOGICAL INFORMATION**

##### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

#### **12.1. Toxicity**

#### **12.2. Persistence and degradability**

#### **12.3. Bioaccumulative potential**

# AUTOTEK VHT ENAMEL MATT BLACK 250ML

## 12.4. Mobility in soil

## 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Collect on absorbent material, place in cardboard kegs and incinerate. Incinerate in suitable combustion chamber. Do not allow runoff to sewer, waterway or ground. Dispose of waste and residues in accordance with local authority requirements.

### SECTION 14: TRANSPORT INFORMATION

#### 14.1. UN number

UN No. (ADR/RID/ADN)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

#### 14.2. UN proper shipping name

Proper Shipping Name                      FLAMMABLE LIQUID, N.O.S. (XYLENE)

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	



#### 14.4. Packing group

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

#### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

#### 14.6. Special precautions for user

EMS	F-E, S-E
Emergency Action Code	•3Y
Hazard No. (ADR)	30
Hazard No. (ADR)	30 Flammable liquid (flash-point between 23°C and 60°C, inclusive) or flammable liquid or solid in the molten state with a flash-point above 60°C, heated to a temperature equal to or above its flash-point, or self heating liquid.

# AUTOTEK VHT ENAMEL MATT BLACK 250ML

Tunnel Restriction Code

(D/E)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations.

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

CHIP for everyone HSG(108).

EU Legislation

Dangerous Preparations Directive 1999/45/EC.

System of specific information relating to Dangerous Preparations. 2001/58/EC.

#### 15.2. Chemical Safety Assessment

### SECTION 16: OTHER INFORMATION

Risk Phrases In Full

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

Hazard Statements In Full

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H412 Harmful to aquatic life with long lasting effects.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure.

H335 May cause respiratory irritation.