

Revision Date 09/05/2012  
Revision 3  
Supersedes date 24/04/2012



**SAFETY DATA SHEET**  
**REDEX DIESEL ONE SHOT 90ml**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name REDEX DIESEL ONE SHOT 90ml  
Product No. RDX0590, RADD0101A

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

Supplier Holt Lloyd International Ltd  
Barton Dock Road  
Stretford  
Manchester  
M32 0YQ - England, UK  
+44 (0) 161 866 4800  
FAX +44 (0) 161 866 4854  
A Holts Car Care Product  
www.holtsauto.com

**1.4. Emergency telephone number**

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Classification (1999/45/EEC) Xn;R65. R10, R44, R52/53, R66.

**2.2. Label elements**

Contains Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene)

Labelling



Harmful

Risk Phrases

R10	Flammable.
R44	Risk of explosion if heated under confinement.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

Safety Phrases

S2	Keep out of the reach of children.
S13	Keep away from food, drink and animal feeding stuffs.
S37	Wear suitable gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

**2.3. Other hazards**

## REDEX DIESEL ONE SHOT 90ml

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene)	60-100%
CAS-No.: 64742-48-9	EC No.: 265-150-3
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65. R10,R66.
2-ETHYL HEXYL NITRATE	10-30%
CAS-No.: 27247-96-7	EC No.: 248-363-6
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xn;R20/21. R44.
Petroleum naphtha heavy aromatic	1-5%
CAS-No.: 64742-94-5	EC No.: 265-198-5
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xn;R65. N;R51/53. R66,R67.
1,2,4-TRIMETHYLBENZENE	< 1%
CAS-No.: 95-63-6	EC No.: 202-436-9
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R20 Xi;R36/37/38 N;R51/53
NAPHTHALENE	< 1%
CAS-No.: 91-20-3	EC No.: 202-049-5
Classification (EC 1272/2008) Acute Tox. 4 - H302 Carc. 2 - H351 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) Carc. Cat. 3;R40 Xn;R22 N;R50/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## REDEX DIESEL ONE SHOT 90ml

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

##### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### Inhalation

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

##### Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

##### Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

##### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

##### Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

#### 5.2. Special hazards arising from the substance or mixture

#### 5.3. Advice for firefighters

##### Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

#### 6.4. Reference to other sections

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Keep away from heat, sparks and open flame.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Do not store near heat sources or expose to high temperatures.

#### 7.3. Specific end use(s)

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

## REDEX DIESEL ONE SHOT 90ml

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1,2,4-TRIMETHYLBENZENE		25 ppm	125			
NAPHTHALENE	WEL	10 ppm	53 mg/m3	15 ppm	80 mg/m3	
Petroleum naphtha heavy aromatic	PT	500 ppm		ppm	2000 mg/m3	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves.

Eye protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Light (or pale). Amber.
Odour	Solvent.
Solubility	Immiscible with water
Relative density	~0.811 @20C
Flash point	44C

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid contact with acids and oxidising substances.

### 10.5. Incompatible materials

## REDEX DIESEL ONE SHOT 90ml

### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### 11.1. Information on toxicological effects

#### Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

#### Ingestion

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

#### Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

#### Eye contact

May cause severe irritation to eyes.

#### Target Organs

Skin Eyes Respiratory system, lungs

---

## SECTION 12: ECOLOGICAL INFORMATION

---

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

---

## SECTION 14: TRANSPORT INFORMATION

---

General LIMITED QUANTITIES to package volumes under 5Lt.

### 14.1. UN number

UN No. (ADR/RID/ADN) 1987

UN No. (IMDG) 1987

UN No. (ICAO) 1987

### 14.2. UN proper shipping name

Proper Shipping Name ALCOHOLS, N.O.S. (Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene), Benzene, 1, 3, 5-trimethyl -)

### 14.3. Transport hazard class(es)

## REDEX DIESEL ONE SHOT 90ml

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	



### 14.4. Packing group

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

### 14.6. Special precautions for user

EMS	F-E, S-D
Tunnel Restriction Code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

---

## SECTION 15: REGULATORY INFORMATION

---

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

### 15.2. Chemical Safety Assessment

---

## SECTION 16: OTHER INFORMATION

---

Revision Date	09/05/2012
Revision	3
Supersedes date	24/04/2012
SDS No.	14308
Date	20/12/2011

## REDEX DIESEL ONE SHOT 90ml

### Risk Phrases In Full

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R36/37/38	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R66	Repeated exposure may cause skin dryness or cracking.
R44	Risk of explosion if heated under confinement.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Hazard Statements In Full

EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET  
REDEX PETROL INJECTOR ONE SHOT 90ml

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1. Product identifier**

Product name REDEX PETROL INJECTOR ONE SHOT 90ml  
Product No. RDX0990, RDX0990EX, RADD0101A

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

Supplier Holt Lloyd International Ltd  
Barton Dock Road  
Stretford  
Manchester  
M32 0YQ - England, UK  
+44 (0) 161 866 4800  
FAX +44 (0) 161 866 4854  
A Holts Car Care Product  
www.holtsauto.com

**1.4. Emergency telephone number**

FR - INRS Tél :+33 (0)1.45.42.59.59 24hrs B - Antigifcentrum Tél: +32.70.245.245 24hrs NL - Rijksinstituut voor Volksgezondheid en Milieuhygiëne: tel. +31 (0)30 274 91 11 24hrs D - +49 (0)89 19240 UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167

SECTION 2: HAZARDS IDENTIFICATION

**2.1. Classification of the substance or mixture**

Classification (1999/45/EEC) Xn;R65. R10, R52/53, R66.

**2.2. Label elements**

Contains Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene)

Labelling



Harmful

Risk Phrases

R10 Flammable.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.

Safety Phrases

S2 Keep out of the reach of children.  
S13 Keep away from food, drink and animal feeding stuffs.  
S37 Wear suitable gloves.  
S46 If swallowed, seek medical advice immediately and show this container or label.  
S51 Use only in well-ventilated areas.  
S56 Dispose of this material and its container to hazardous or special waste collection point.



## REDEX PETROL INJECTOR ONE SHOT 90ml

### 2.3. Other hazards

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene)	60-100%
CAS-No.: 64742-48-9	EC No.: 265-150-3
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65. R10,R66.
Solvent Naphtha (petroleum) heavy aromatic	5-10%
CAS-No.: 64742-94-5	EC No.: 265-198-5
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xn;R65. N;R51/53. R66,R67.
Polyolefin alkylphenol alkylamine	5-10%
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xi;R36/38.
Benzene, 1,3,5-trimethyl -	1-5%
CAS-No.: 108-67-8	EC No.: 203-604-4
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) R10 Xi;R37 N;R51/53
2-ETHYL HEXANOL	1-5%
CAS-No.: 104-76-7	EC No.: 203-234-3
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xi;R36/38.

## REDEX PETROL INJECTOR ONE SHOT 90ml

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA		1-5%
CAS-No.: 64742-95-6	EC No.: 265-199-0	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R37. N;R51/53. R66,R67,R10.	
1,2,4-TRIMETHYLBENZENE		1-5%
CAS-No.: 95-63-6	EC No.: 202-436-9	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R20 Xi;R36/37/38 N;R51/53	
NAPHTHALENE		< 1%
CAS-No.: 91-20-3	EC No.: 202-049-5	
Classification (EC 1272/2008) Acute Tox. 4 - H302 Carc. 2 - H351 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) Carc. Cat. 3;R40 Xn;R22 N;R50/53	
PROPYLBENZENE		< 1%
CAS-No.: 103-65-1	EC No.: 203-132-9	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R65 Xi;R37 N;R51/53	
CUMENE		< 1%
CAS-No.: 98-82-8	EC No.: 202-704-5	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R10 Xn;R65 Xi;R37 N;R51/53	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## REDEX PETROL INJECTOR ONE SHOT 90ml

---

### SECTION 4: FIRST AID MEASURES

---

#### 4.1. Description of first aid measures

##### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### Inhalation

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

##### Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

##### Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

##### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

---

### SECTION 5: FIREFIGHTING MEASURES

---

#### 5.1. Extinguishing media

##### Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

#### 5.2. Special hazards arising from the substance or mixture

#### 5.3. Advice for firefighters

##### Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out.

---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

---

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

#### 6.4. Reference to other sections

---

### SECTION 7: HANDLING AND STORAGE

---

#### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

#### 7.3. Specific end use(s)

---

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

#### 8.1. Control parameters

## REDEX PETROL INJECTOR ONE SHOT 90ml

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1,2,4-TRIMETHYLBENZENE		25 ppm	125			
CUMENE	WEL	25 ppm(Sk)	125 mg/m3(Sk)	50 ppm(Sk)	250 mg/m3(Sk)	
NAPHTHALENE	WEL	10 ppm	53 mg/m3	15 ppm	80 mg/m3	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves.

Eye protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Light (or pale). Amber.
Odour	Solvent.
Solubility	Immiscible with water
Relative density	~0.797 @20C
Flash point	44C

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid contact with acids and oxidising substances.

### 10.5. Incompatible materials

## REDEX PETROL INJECTOR ONE SHOT 90ml

### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### 11.1. Information on toxicological effects

#### Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

#### Ingestion

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

#### Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

#### Eye contact

May cause severe irritation to eyes.

#### Target Organs

Skin Eyes Respiratory system, lungs

---

## SECTION 12: ECOLOGICAL INFORMATION

---

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

---

## SECTION 14: TRANSPORT INFORMATION

---

General LIMITED QUANTITIES to package volumes under 5Lt.

### 14.1. UN number

UN No. (ADR/RID/ADN)	1987
UN No. (IMDG)	1987
UN No. (ICAO)	1987

### 14.2. UN proper shipping name

Proper Shipping Name	ALCOHOLS, N.O.S. (Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene), Benzene, 1, 3, 5-trimethyl -)
----------------------	--

### 14.3. Transport hazard class(es)

## REDEX PETROL INJECTOR ONE SHOT 90ml

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	



### 14.4. Packing group

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

### 14.6. Special precautions for user

EMS	F-E, S-D
Tunnel Restriction Code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

---

## SECTION 15: REGULATORY INFORMATION

---

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

### 15.2. Chemical Safety Assessment

---

## SECTION 16: OTHER INFORMATION

---

Revision Date	09/05/2012
Revision	4
Supersedes date	24/04/2012
SDS No.	14305
Date	19/12/2011

## REDEX PETROL INJECTOR ONE SHOT 90ml

### Risk Phrases In Full

R10	Flammable.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R40	Limited evidence of a carcinogenic effect.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Hazard Statements In Full

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H302	Harmful if swallowed.
H412	Harmful to aquatic life with long lasting effects.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H410	Very toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.